

## Kustannustehokas digitaalinen paino - OKI ES9410



Haluatko tehdä asiakkaillesi pieniä tai kustomoituja painoeriä? Haluatko pysyvän laadun, toimintavarmuuden ja käytön helppouden? Haluatko hyödyntää uusia formaatteja kuten 1 200 mm pituisia banderolleja? Ratkaisu on OKI ES9410!

Asiakkaasi arvioivat jatkuvasti painotöiden laatua, mikä tarkoittaa, että olet heidän silmissään yhtä hyvä kuin viimeisin painotyösi. Kun olet siirtymässä digitaaliseen painamiseen, haluat varmistaa, että uskallat laittaa näihinkin töihin nimesi pantiksi.

### Uudella OKI ES9410 -laitteella uskallat!

OKI ES9410 on "Entry-Level Digital Press" -laite, jonka ansiosta siirtyminen uuteen tekniikkaan ja formaatteihin on mahdollisimman helppoa ja kustannustehokasta. OKIn ainutlaatuinen LED-tekniikka yhdistettynä uuteen tasalaatuiseen MicroCrushed HD -väriaineeseen varmistaa, että asiakkaasi nauttivat upeasta painolaadusta – ja tulevat varmasti takaisin!

**Sovi ilmainen kartoitus!**

Vesa Olkkonen ■ p. (014) 33 44 500

Vasarakatu 1, 40320 Jyväskylä ■ p. (014) 33 44 500 ■ [www.toimistonova.fi](http://www.toimistonova.fi) ■ [info@toimistonova.fi](mailto:info@toimistonova.fi)

**Toimisto**  
**Nova**

## Kustannustehokas digitaalinen paino - OKI ES9410



### OKI ES9410 lyhyesti

- Nopeus: 31 väri- / 36 mustavalkosivua min. (A4)
- Paperikoot: A3, SRA3 (maks. 328 x 457 mm), A4, A5, A6, jopa 1 200 mm pituiset banderollit
- Paperipainot: 300 g/m<sup>2</sup> asti
- Ohjaukset: PCL5c, PCL XL (Väri), Adobe PostScript 3 suoralla PDF-tulostuksella, SIDM
- Värihallinta: sisäänrakennettu Graphics Pro ICC-profiileita ja värintäsmäystä varten
- Yhteensopivuus: EFI Colorproof XF RIP ja EFI Fiery XF production RIP
- 3 vuoden ilmainen Onsite-takuu

#### TULOSTIN

Print speed	A4: 31ppm colour, 36ppm mono; A3: 16ppm colour, 20ppm mono
Time to first print	10.5 seconds colour, 9 seconds mono
Warm up time	85 seconds or less from power on
Processor speed	PowerPC 750 800MHz

#### LIITÄNNÄT JA OHJELMISTOT

Connectivity	IEEE 1284 Bi-directional Parallel, Hi-Speed USB 2.0, 10Base-T/100Base-TX/1000Base-T Ethernet
Printer languages	PCL5c, PCL XL (Colour), Adobe PostScript 3 with direct PDF Printing (v1.6), SIDM
Network & protocols	All major network protocols supported via ethernet card with internal web server for printer and network card set-up and management. TCP/IP: ARP, RARP, IPv4/v6, ICMPv4/v6, TCP, UDP, LPR, FTP, TELNET, HTTP(IPP), BOOTP, DHCP, SNMPv1/v3, DNS, DDNS, UPnP, Bonjour, WINS, SSL/TLS, SMTP, POP3, SNTP, WSDPrint, JetDirect protocols. NetWare 3.x, 4.x, 5.x and 6 with full NDS and NDPS support:- PServer, RPrinter, NDPS supported via dedicated OKI NDPS Gateway. AppleTalk:- ELAP, AARP, DDP, AEP, NBP, ZIP, RTMP, ATP, PAP. NetBEUI:- SMB, NetBIOS. Other:EAP
OS Compatibility <sup>1</sup>	Windows Vista (32-bit & 64-bit) / 2000 Workstation (SP3 or later) / 2000 Professional (SP3 or later) / Server 2000 (SP3 or later) / Advanced Server 2000 (SP3 or later) / XP Professional / XP Professional x64 / XP Home / Server 2003 / Server 2003x64 / Server 2008 / Server 2008x64 / Server 2000 (SP4) + Citrix MetaFrame XP Presentation Server Feature Release 4 / Server 2003 Standard Edition + Citrix MetaFrame XP Presentation Server Feature Release 4; Mac OS X 10.3 - 10.6.1
Advanced networking and security	IPv6, 802.1x authentication, SNMPv3, SSL3/TLS HTTPS encryption, Data Encryption, MAC filtering, IP filtering, Secure Erase, Secure Print
Utility Suite <sup>1</sup>	Print Control Server <sup>2</sup> , Print Control Client, PrintSuperVision.net <sup>2</sup> , Template Manager <sup>2</sup> , Storage Device Manager <sup>2</sup> , Profile Assistant <sup>2</sup> , Color Correct, PS Gamma Adjuster, PDF Direct Print

#### KIRJASINTYYPIIT

Printer fonts	86 scalable PCL fonts, 1 bitmap font, 10 TrueType fonts, 136 Adobe PostScript Type 1 fonts
Barcode	Barcode with Checksum support

#### TULOSTUSLAATU

Resolution	ProQ2400 Multi-level technology, 1200 x 600dpi
Enhancements	Auto Colour Balance, Auto Registration, Auto Media Detect

<sup>1</sup> Check local OKI Executive Series website for latest driver releases and OS compatibility

<sup>2</sup> Windows only

<sup>3</sup> Including all consumables

#### PAPERINKÄSITTELY

Paper capacity	Tray 1: 530 sheets of 80gsm; Multi-purpose tray: 230 sheets of 80gsm
Paper capacity optional trays	Tray 2: 530 sheets of 80gsm; Tray 3: 530 sheets of 80gsm; High Capacity Feeder: 1,590 sheets of 80gsm
Maximum paper capacity	2,880 sheets of 80gsm
Paper sizes	Tray 1/2/3: A3, SRA3 (up to 328 x 457mm), A4, A5, A6; Multi-purpose tray: A3, SRA3 (up to 328 x 457mm), A4, A5, A6, Custom size: Width 79.2 - 328mm Length 90 - 1,200mm; High Capacity Feeder: A3, SRA3 (up to 328 x 457mm), A4, A5, A6
Paper weight	Tray 1/2/3: 64 to 216gsm; Multi-purpose tray: 64 to 300gsm; Duplex: 64 to 188gsm; High Capacity Feeder: 64 to 216gsm
Duplex	Standard
Paper output	500 sheets face down tray, 200 sheets face up tray

#### YLEISET OMINAISUUDET

Memory	Standard RAM: 512MB; Maximum RAM: 1024MB Hard Disk Drive: 40GB
Operating conditions	Temperature/Humidity: 10°C to 32°C (17°C to 27°C recommended) / 20% to 80% RH (50% to 70% RH recommended) Storage: -20°C to 45°C, 10% to 90%RH
Power supply	Single phase 220 to 240VAC, frequency 50Hz +/- 2Hz
Power consumption	Typical: 750W; Max: 1500W; Idle: 200W (average); Power Save: <33W
Noise level	Operating: 54dB(A) or less; Standby: 42dB(A) or less; Power save: 28dB(A) after 30 mins
Dimensions (HxWxD)	471 x 654.5 x 623mm
Weight <sup>3</sup>	81kg
Product order number	ES9410dn: 01267201

#### LISÄVARUSTEET

2nd/3rd paper tray	42831303
2nd/3rd lockable paper tray	01216601
Duplex	42797203
High Capacity Feeder	42831503
Cabinet	09004256
Memory	256MB: 01182901; 512MB: 01182902
4-tray Finisher	01166702 (High Capacity Feeder required)
5-tray Finisher	01166802 (High Capacity Feeder & 2nd paper tray required)
2-hole Finisher-Punch Unit	01176001 (Finisher unit required)
4-hole Finisher-Punch Unit	01176002 (Finisher unit required)
4-hole (Swedish) Finisher-Punch Unit	01176003 (Finisher unit required)

**Sovi ilmainen kartoitus!**

Vesa Olkkonen ■ p. (014) 33 44 500

Vasarakatu 1, 40320 Jyväskylä ■ p. (014) 33 44 500 ■ www.toimistonova.fi ■ info@toimistonova.fi

**Toimisto**  
**Nova**